



PROJECT		REF		REV	ITEM CODE	
LOCATION		DATE			PAGE	

## SANITARY WARE SPECIFICATION SHEET

<p><b>Item Descriptions</b></p> <p>GROHE (Germany) "Europlus E" Infra-red electronic basin tap 1/2" (DC Verison); nominated flow rate <b>1.7 L/min</b> in WELS <b>Grade 1</b>; Registration No. TN 21-0020</p>	<p><b>Illustration/ Drawing</b></p> 
<p><b>Dimensions</b></p> <p>L154 x W52 x H149 mm</p>	
<p><b>Model</b></p> <p>36208001</p>	
<p><b>Finish</b></p> <p>Chrome Plated</p>	
<p><b>Manufacturer</b></p> <p>GROHE Limited</p>	
<p><b>Supplier</b></p> <p>Acme Sanitary Ware Co. Ltd</p>	
<p><b>Contact Tel/Fax</b></p> <p>Mr. Eric Wong/ Mr. Don Yuen</p>	
<p><b>E-mail</b></p> <p>(852) 2388-7171 / (852) 2710-8012</p>	
<p><b>Website</b></p> <p>acme@acmesanitary.com.hk</p>	
<p><b>Europlus E</b> <b>Infrared electronic basin mixer 1/2" without mixing device</b> <b>battery power supply 6 V,lithium-battery, type CR-P2</b> CE approved,single hole installation LongLife battery electronic battery lifetime: approx. 7 years (150 actuations a day) 7 pre-set programs: with 24/72 hours autoflush time or user dependent,with cleaning mode safety stop after 60 sec. additional functions by remote control: adjustable flow time adjustable reflection range by remote activation of thermal disinfection for 3.5 or 11 min by hand multistage battery status display, mousseur 5.7 l/min flexible connecting hoses dirt strainer,non-return valve type of protection faucet IP 59K noise classification 1 in accordance with DIN4109 for cold or premixed water <b>GROHE EcoJoy™</b> Technology for less water and perfect flow <b>GROHE StarLight®</b> chrome finish minimum pressure 1,0 bar <b>solenoid valve</b>,rapid-installation-system</p>	

**Note:**

\* All information of the above is for the reference only. No prior notice is made if any changes.

註冊號碼 (Registration No.):

TN 21-0020



自願參與用水效益標籤計劃 - 水龍頭  
Voluntary Water Efficiency Labelling Scheme - Water Taps




茲證明  
This is to certify that

將下列水龍頭在本計劃內註冊：  
has registered the following water tap under this scheme :

牌 子 / Brand	:	Grohe
型 號 / Model	:	36208XX1 + 403986040
種 類 / Type	:	Non-mixing
原產地 / Country or Region Origin	:	Germany (Tap & Flow Controller)

XX – denotes the code of colour

在用水效益標籤上展示的標誌 <i>Symbolic Presentation on the Water Efficiency Label</i>	:	 滴水點 <i>Water droplet(s)</i>
用水效益級別 <i>Water Efficiency Grade</i>	:	1 with additional merit*
耗水量 <i>Water Consumption</i>	:	1.7 公升/分鐘 <i>litres/minute</i>

\*with additional merit of "Automatic closing mechanism"

簽發日期：  
Date of Issue: 8 March 2021

 水務署  
Water Supplies Department



水務署署長(張業駒代行)  
for Director of Water Supplies



水務署

Waterworks Department



事務大樓 48 樓

Gloucester Road, Wan Chai, Hong Kong

本署檔號 : ( 2 ) in WSD 3321/2020 T/J(829/2020)  
Our ref.  
來函檔號 :  
Your ref.

電話 :  
Tel.  
傳真 : 2824 0578  
Fax.

18 August 2020



**Approval of "GROHE" Sensor Tap  
(General Acceptance No. C20200678)**

Your letter ref. WRC/2281 dated 6 July 2020 refers.

Having considered the test report ref. J24767A issued on 4 December 2019 by Nutek Systems (HK) Ltd., this Authority accepts that the fitting described below complies with, and its use when correctly installed does not contravene, the Waterworks Ordinance and Regulations.

**Name of Manufacturer:** Grohe AG

**Country of Origin:** Germany

**Brand:** Grohe

**Details of Fitting:** 3/8" Infrared electronic basin tap

**Model:** 36208XX1  
(where the digits "XX" denote the code of colour)

**Body Markings:** **GROHE**

**Expiry Date:** 5 November 2024





This Authority hereby permits the use of the above fitting in fresh water plumbing systems subject to full adherence to Waterworks installation requirements. In particular, you are required to draw your customers' attention to the following requirement-

"A stop cock or gate valve must be installed at the upstream of the fitting for manual isolation of water supply." AND

"The main voltage operated sensor valve should comply with the electricity safety regulation for applications in bathroom, toilet etc."

A condition of this acceptance is that the fitting to be installed shall be replicas of the sample as certified by the testing agent mentioned above and without modifications. This acceptance may be withdrawn at any time if the standard of the fitting installed fail to meet that of the approved sample or if the fitting is found to be unsuitable for use in fresh water plumbing systems.

This acceptance is only applicable to the main body of the fitting, unless otherwise specified.

For the use of the fitting in any project, the General Acceptance Number of this letter must be quoted as a means of identification of acceptance of the fitting by this Authority.

Should you have any enquiries, please contact our Engineer Mr. Terry KUNG at tel. no. 3583 4086.

Yours faithfully,



(CHAN Chung-kun)

for Director of Water Supplies

Encl.

c.c.      WSD 3321/1/82   ] - without catalogue  
             ME/MC           ] - with soft copy only