



PROJECT		REF		REV	ITEM CODE	
LOCATION		DATE			PAGE	

SANITARY WARE SPECIFICATION SHEET

<p>Item Descriptions</p> <p>Dimensions</p> <p>Model</p> <p>Finish</p> <p>Manufacturer</p> <p>Country of Origin</p> <p>Supplier</p> <p>Contact Tel/Fax</p> <p>E-mail</p> <p>Website</p>	<p>GROHE (Germany) "Eurosmart Cosmopolitan E" Infra-red electronic wall thermaostatic basin tap with concealed mounting box; nominated flow rate 1.9 L/min in WELS Grade 1; Registration No. TM 22- 0157</p> <p>L232 x W120 x H195 mm</p> <p>36334SD0 (Thermaostatic Basin Mixer) 36336001 (Mounting Box)</p> <p>SuperSteel</p> <p>GROHE Limited Germany</p> <p>Acme Sanitary Ware Co. Ltd Mr. Eric Wong/ Mr. Don Yuen (852) 2388-7171 / (852) 2710-8012 acme@acmesanitary.com.hk www.acmesanitary.com.hk</p>	<p>Illustration/ Drawing</p>  
<p>36334SD0 (Basin mixer) Infra-red electronic wall basin tap with infrared sensor for bi-directional communication for monitoring, configuration and servicing for cold or premixed water with transformer 100-230 V AC, 50-60 Hz, 6 V DC laminar mousseur 9 l/min stainless steel escutcheon SuperSteel spout 172 mm 7 pre-set programs auto flush thermal disinfection cleaning mode additional functions and precise settings by remote control 36 407 set for final installation for concealed fitting box 36 336 001/36 337 001 CE approved noise classification 1 in accordance with DIN4109 min. recommended pressure 1.0 bar</p>	<p>36336001 (Mounting Box) Euroeco Cosmopolitan E Concealed mounting box with integrated pre-adjustable thermostatic mixer wall installation suitable for IR-sets for final installation 2 stop valves non-return valve suitable for 36 410 000, 36 334 SD0, 36 335 SD0, 36 273 000 allows for waterproofing of wall construction surrounding the concealed body with sealing sleeve</p> 	

Note:

* All information of the above is for the reference only. No prior notice is made if any changes.

註冊號碼 (Registration No.): TM 22-0157



自願參與用水效益標籤計劃 - 水龍頭
Voluntary Water Efficiency Labelling Scheme - Water Taps




茲證明

This is to certify that

將下列水龍頭在本計劃內註冊：
has registered the following water tap under this scheme :

牌子 / Brand	:	Grohe
型號 / Model	:	36336001 + 36334XXX + 403986040
種類 / Type	:	Mixing
原產地 / Country or Region Origin	:	Germany (Mixer & Flow Controller)

XXX – denotes the code of colour

在用水效益標籤上展示的標誌 <i>Symbolic Presentation on the Water Efficiency Label</i>	:		滴水點 <i>Water droplet(s)</i>
用水效益級別 <i>Water Efficiency Grade</i>	:	1	with additional merit*
耗水量 <i>Water Consumption</i>	:	1.9	公升/分鐘 <i>litres/minute</i>

*with additional merit of "Automatic closing mechanism" & "Super water efficient"

簽發日期：
Date of Issue:

26 July 2022

 水務署
Water Supplies Department



水務署署長(林麗恒代行)
for Director of Water Supplies



水務署
Water Supplies Department

總部 Headquarters

香港灣仔告士打道七號入境事務大樓 48 樓

Immigration Tower, 7 Gloucester Road, Wan Chai, Hong Kong

本
On
來函
Your re,



3321/2021 T/J(1895/2021)

電話

Tel. :

傳真

Fax. :

2824 0578

21 March 2022



Approval of "GROHE" Sensor Mixer (General Acceptance No. C20220213)

Your letters ref. WRC/2730 and C-WSD/0896 dated 28 December 2021 and 28 January 2022 respectively refer.

Having considered the test reports ref. 210784PC210216A and 202535EN202542(3) issued on 27 January 2022 and 8 February 2021 by Fugro Technical Services Limited, this Authority accepts that the fitting described below complies with, and its use when correctly installed does not contravene, the Waterworks Ordinance and Regulations.

Name of Manufacturer: Grohe AG

Country of Origin: Germany

Brand: Grohe

Details of Fitting: 1/2" Wall mounted sensor basin mixer with 1 no. of flexible hose

Model: 36336001 + 36334XXX
(where "XXX" denote the code of colour)

Body Markings:



Expiry Date: 19 November 2025

This Authority hereby permits the use of the above fitting in fresh water plumbing systems subject to full adherence to Waterworks installation requirements. In particular, you are required to draw your customers' attention to the following requirement-

"The cold water supply to the fitting shall be drawn from the same source that supplies the hot water apparatus so as to provide a balanced pressure and to obviate the risk of scalding in the event of a restriction or failure in the water supply."

"A stop cock or gate valve must be installed at the upstream of the fitting for manual isolation of water supply." AND

"The main voltage operated sensor valve should comply with the electricity safety regulation for applications in bathroom, toilet etc."

A condition of this acceptance is that the fitting to be installed shall be replicas of the sample as certified by the testing agent mentioned above and without modifications. This acceptance may be withdrawn at any time if the standard of the fitting installed fail to meet that of the approved sample or if the fitting is found to be unsuitable for use in fresh water plumbing systems.

This acceptance is only applicable to the main body of the fitting, unless otherwise specified.

For the use of the fitting in any project, the General Acceptance Number of this letter must be quoted as a means of identification of acceptance of the fitting by this Authority.

Should you have any enquiries, please contact our Engineer Ms Winnie LO at tel. no. 3583 4086.

Yours faithfully,



(YAU Hau Yin)

for Director of Water Supplies

Encl.

c.c. WSD 3321/1/82] - without catalogue
ME/MC] - with soft copy only