

# Acme Sanitary Ware Co. Ltd.

1/F, Acme Building, 22-28 Nanking Street, Kowloon, Hong Kong Tel: 2388 7171 Fax: 2710 8012  ${\bf Email: acme@acmes an itary. com. hk}$ Since 1949 Website: www.acmesanitary.com.hk



PROJECT	REF	REV	ITEM CODE	
	DATE		PAGE	

### SANITARY WARE SPECIFICATION SHEET

mounted time flow basin tap; nominated flow rate 3 L/min in WELS Grade 2; Registration No. TN 20-0081  Model 740500  Material/ Finish Brass/ Chrome Plated  Manufacturer Delabie (France)  Source Acme Sanitary Ware Co. Ltd Mr. Eric Wong/ Mr. Don Yuen  Contact Tel/Fax (852) 2388-7171 / (852) 2710-8012  acme@acmesanitary.com.hk  Website www.acmesanitary.com.hk  TEMPOSOFT 2 - Ref. 740500  Deck-mounted time flow basin tap: Soft-touch operation. Time flow 7 seconds. Flow rate pr-est at 3 lpm at 3 bar, can be adjusted from 1.5 to 6 lpm. Tamperproof scale-resistant flow straightener. Solid chrome-plated brass body M1/2". Flixing with back-nut. Supplied with red and blue markers.  Connector M1/2" ADVANTAGES  Technology Time flow Soft touch operation Drop height 75mm Spout length 100mm Flow rate 3 lpm 100mm StanDaRDS AND CERTIFICATIONS Smooth design  Smooth design	-		"TEMPOSOFT 2" Deck-	Illustration/ Drawing		
Model 740500  Material/ Finish Brass/ Chrome Plated  Manufacturer Delabie (France)  Source Acme Sanitary Ware Co. Ltd Mr. Eric Wong/ Mr. Don Yuen  Contact Tel/Fax (852) 2388-7171 / (852) 2710-8012 acme@acmesanitary.com.hk  Website www.acmesanitary.com.hk  TEMPOSOFT 2 - Ref. 740500 Deck-mounted time flow basin tap: Soft-touch operation. Time flow 7 seconds. Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.5 to 6 lpm. Tamperproof scale-resistant flow straightener. Solid chrome-plated brass body M1/2". Fixing with back-nut. Supplied with red and blue markers.  Connector M1/2" ADVANTAGES Technology Time flow Soft-touch operation Drop height 75mm Spout length 100mm Available Smooth design  Smooth design  Smooth design			-			
Model 740500  Material/ Finish Brass/ Chrome Plated  Manufacturer Delabie (France)  Source Acme Sanitary Ware Co. Ltd Mr. Eric Wong/ Mr. Don Yuen  Contact Tel/Fax (852) 2388-7171 / (852) 2710-8012  acme@acmesanitary.com.hk  Website www.acmesanitary.com.hk  TEMPOSOFT 2 - Ref. 740500  Deck-mounted time flow basin tap: Soft-touch operation. Time flow 7 seconds Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.5 to 6 lpm. Tamperproof scale-resistant flow straightener. Solid chrome-plated brass body M1/2". Fixing with back-nut. Supplied with red and blue markers.  Connector M1/2" ADVANTAGES Technology Time flow Soft-touch operation  Drop height 75mm Spout length 100mm Seconds Smooth design  Smooth design			o Graue 2; Registration No. 1N	用水及益原 Efficiency (Label		
Material/ Finish  Brass/ Chrome Plated  Manufacturer  Delabie (France)  Source  Acme Sanitary Ware Co. Ltd Mr. Eric Wong/ Mr. Don Yuen  Contact Tel/Fax  (852) 2388-7171 / (852) 2710-8012  E-mail acme@acmesanitary.com.hk  Website www.acmesanitary.com.hk  TEMPOSOFT 2 - Ref. 740500  Deck-mounted time flow basin tap: Soft-touch operation. Time flow 7 seconds. Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.5 to 6 lpm. Tamperproof scale-resistant flow straightener. Solid chrome-plated brass body M1/2". Fixing with back-nut. Supplied with red and blue markers.  Connector  M1/2"  ADVANTAGES  Technology  Time flow Soft touch operation  Tomp height  75mm  Spout length 100mm  Flow rate  3 lpm Smooth design  Smooth design						
Material/ Finish  Brass/ Chrome Plated  Manufacturer  Delabie (France)  Source  Acme Sanitary Ware Co. Ltd Mr. Eric Wong/ Mr. Don Yuen  Contact Tel/Fax  (852) 2388-7171 / (852) 2710-8012  E-mail acme@acmesanitary.com.hk  Website www.acmesanitary.com.hk  TEMPOSOFT 2 - Ref. 740500  Deck-mounted time flow basin tap: Soft-touch operation. Time flow 7 seconds. Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.5 to 6 lpm. Tamperproof scale-resistant flow straightener. Solid chrome-plated brass body M1/2". Fixing with back-nut. Supplied with red and blue markers.  Connector  M1/2" ADVANTAGES  Technology Time flow Soft touch operation  Orop height 75mm Spout length 100mm Flow rate Simooth design  Smooth design				B N 2		
Material/ Finish  Manufacturer  Delabie (France)  Source  Acme Sanitary Ware Co. Ltd Mr. Eric Wong/ Mr. Don Yuen  Contact Tel/Fax  (852) 2388-7171 / (852) 2710-8012  E-mail  acme@acmesanitary.com.hk  Website  Www.acmesanitary.com.hk  TEMPOSOFT 2 - Ref. 740500  Deck-mounted time flow basin tap: Soft-touch operation. Time flow 7 seconds. Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.5 to 6 lpm. Tamperproof scale-resistant flow straightener. Solid chrome-plated brass body M1/2*. Fixing with back-nut. Supplied with red and blue markers.  Connector  M1/2*  ADVANTAGES  Technology  Time flow Soft-touch operation  Orop height 75mm Spout length 100mm Flow rate 3 lpm Smooth design  Smooth design	Model	740500		TADY WADE		
Manufacturer  Delabie (France)  Acme Sanitary Ware Co. Ltd Mr. Eric Wong/ Mr. Don Yuen  Contact Tel/Fax  (852) 2388-7171 / (852) 2710-8012  E-mail acme@acmesanitary.com.hk  Website www.acmesanitary.com.hk  TEMPOSOFT 2 - Ref. 740500  Deck-mounted time flow basin tap: Soft-touch operation. Time flow 7 seconds. Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.5 to 6 lpm. Tamperproof scale-resistant flow straightener. Solid chrome-plated brass body M1/2". Fixing with back-nut. Supplied with red and blue markers.  Connector M1/2" ADVANTAGES Technology Time flow Soft-touch operation Drop height 75mm Spout length 100mm Plow rate 3 lpm Smooth design  Smooth design				OM The same		
Source Acme Sanitary Ware Co. Ltd Mr. Eric Wong/ Mr. Don Yuen  Contact Tel/Fax (852) 2388-7171 / (852) 2710-8012 acme@acmesanitary.com.hk Website www.acmesanitary.com.hk  TEMPOSOFT 2 - Ref. 740500 Deck-mounted time flow basin tap: Soft-touch operation. Time flow 7 seconds. Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.5 to 6 lpm. Tamperproof scale-resistant flow straightener. Solid chrome-plated brass body M1/2°. Fixing with back-nut. Supplied with red and blue markers.  ADVANTAGES Technology Time flow Soft-touch operation Drop height 75mm Spout length 100mm Flow rate 3 lpm Smooth design  Smooth design	Material/ Finish	Brass/ Chrome Pl	ated			
Source Acme Sanitary Ware Co. Ltd Mr. Eric Wong/ Mr. Don Yuen  Contact Tel/Fax (852) 2388-7171 / (852) 2710-8012 acme@acmesanitary.com.hk Website www.acmesanitary.com.hk  TEMPOSOFT 2 - Ref. 740500 Deck-mounted time flow basin tap: Soft-touch operation. Time flow 7 seconds. Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.5 to 6 lpm. Tamperproof scale-resistant flow straightener. Solid chrome-plated brass body M1/2°. Fixing with back-nut. Supplied with red and blue markers.  ADVANTAGES Technology Time flow Soft-touch operation Drop height 75mm Spout length 100mm Flow rate 3 lpm Smooth design  Smooth design	Manufacturar	Dalahia (Eranga)				
Mr. Eric Wong/ Mr. Don Yuen  Contact Tel/Fax (852) 2388-7171 / (852) 2710-8012  E-mail acme@acmesanitary.com.hk  Website www.acmesanitary.com.hk  TEMPOSOFT 2 - Ref. 740500  Deck-mounted time flow basin tap: Soft-touch operation. Time flow 7 seconds. Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.5 to 6 lpm. Tamperproof scale-resistant flow straightener. Solid chrome-plated brass body M1/2". Fixing with back-nut. Supplied with red and blue markers.  Connector M1/2" ADVANTAGES Technology Time flow Soft-touch operation Drop height 75mm Spout length 100mm  Southeagth 100mm Smooth design  Smooth design	ivianuracturer	Delable (France)				
Mr. Eric Wong/ Mr. Don Yuen  Contact Tel/Fax (852) 2388-7171 / (852) 2710-8012  E-mail acme@acmesanitary.com.hk  Website www.acmesanitary.com.hk  TEMPOSOFT 2 - Ref. 740500  Deck-mounted time flow basin tap: Soft-touch operation. Time flow 7 seconds. Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.5 to 6 lpm. Tamperproof scale-resistant flow straightener. Solid chrome-plated brass body M1/2". Fixing with back-nut. Supplied with red and blue markers.  Connector M1/2" ADVANTAGES Technology Time flow Soft-touch operation Drop height 75mm Spout length 100mm  Southeagth 100mm Smooth design  Smooth design	Source	Acme Sanitary W	are Co. Ltd			
Contact Tel/Fax  E-mail  acme@acmesanitary.com.hk  Website  TEMPOSOFT 2 - Ref. 740500  Deck-mounted time flow basin tap: Soft-touch operation. Time flow 7 seconds. Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.5 to 6 lpm. Tamperproof scale-resistant flow straightener. Solid chrome-plated brass body M1/2". Fixing with back-nut. Supplied with red and blue markers.  Connector  M1/2" ADVANTAGES  Technology Time flow Soft-touch operation Drop height 75mm Spout length 100mm Flow rate 3 lpm Smooth design  Smooth design		-				
E-mail acme@acmesanitary.com.hk  Website www.acmesanitary.com.hk  TEMPOSOFT 2 - Ref. 740500  Deck-mounted time flow basin tap: Soft-touch operation. Time flow 7 seconds. Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.5 to 6 lpm. Tamperproof scale-resistant flow straightener. Solid chrome-plated brass body M1/2". Fixing with back-nut. Supplied with red and blue markers.  Connector M1/2" ADVANTAGES Technology Time flow Soft-touch operation Drop height 75mm Spout length 100mm Flow rate 3 lpm Smooth design  Smooth design		3				
Website www.acmesanitary.com.hk  TEMPOSOFT 2 - Ref. 740500 Deck-mounted time flow basin tap: Soft-touch operation. Time flow 7 seconds. Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.5 to 6 lpm. Tamperproof scale-resistant flow straightener. Solid chrome-plated brass body M1/2". Fixing with back-nut. Supplied with red and blue markers.  Connector M1/2" ADVANTAGES Technology Time flow Soft-touch operation Drop height 75mm Spout length 100mm Flow rate 3 lpm Smooth design  Smooth design	Contact Tel/Fax	(852) 2388-7171				
TEMPOSOFT 2 - Ref. 740500  Deck-mounted time flow basin tap: Soft-touch operation. Time flow 7 seconds. Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.5 to 6 lpm. Tamperproof scale-resistant flow straightener. Solid chrome-plated brass body M1/2". Fixing with back-nut. Supplied with red and blue markers.  Connector  M1/2" ADVANTAGES  Technology Time flow Soft-touch operation  Prop height Tomm Spout length 100mm Flow rate 3 lpm Smooth design  STANDARDS AND CERTIFICATIONS Soft-touch design	E-mail	acme@acmesanit				
Deck-mounted time flow basin tap: Soft-touch operation. Time flow 7 seconds. Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.5 to 6 lpm. Tamperproof scale-resistant flow straightener. Solid chrome-plated brass body M1/2". Fixing with back-nut. Supplied with red and blue markers.  Connector  M1/2" ADVANTAGES  Technology Time flow Drop height 75mm Spout length 100mm  Flow rate 3 lpm STANDARDS AND CERTIFICATIONS Soft-touch operation Smooth design	Website	www.acmesanitai	ry.com.hk			
Drop height 75mm  Spout length 100mm  Flow rate 3 lpm  STANDARDS AND CERTIFICATIONS Smooth design	Soft-touch operation. Time flow 7 seconds. Flow rate pre-set at 3 lpm a Tamperproof scale-resistan Solid chrome-plated brass b Fixing with back-nut. Supplied with red and blue	at 3 bar, can be ad at flow straightene body M1/2". markers.	r.			
Drop height 75mm  Spout length 100mm  Flow rate 3 lpm  STANDARDS AND CERTIFICATIONS Smooth design				•		
Spout length 100mm  Flow rate 3 lpm  STANDARDS AND CERTIFICATIONS Smooth design  Smooth design			Soit-touch operation	4 (0)		
			Water savings up to 85 %	1/2		
	Flow rate	3 lpm	Smooth decian	_ 100 _ E		
	STANDARDS AND CERTIFICATION	ONS 🥌 WRAS 📗		50		
	WARRANTY					

Note:

<sup>\*</sup> All information of the above is for the reference only. No prior notice is made if any changes.

TN 20-0081



## 自願參與用水效益標籤計劃 - 水龍頭 Voluntary Water Efficiency Labelling Scheme - Water Taps





#### 茲證明 This is to certify that

將下列水龍頭在本計劃內註冊: has registered the following water tap under this scheme:

/ Brand Delabie / Model 740500

/ Type Non-mixing

/ Country or Region Origin UK 原產地

在用水效益標籤上展示的標誌

Symbolic Presentation on the Water Efficiency Label

滴水點 Water droplet(s)

用水效益級別

Water Efficiency Grade

with additional merit\*

耗水量

Water Consumption

3.0

2

公升/分鐘 litres/minute

\*with additional merit of "Automatic closing mechanism"

簽發日期: Date of Issue: 30 November 2020





水務署署長(張業駒代行) for Director of Water Supplies



總部 Headquarters

士打道七號入境事務大樓 48 樓

ion Tower, 7 Gloucester Road, Wan Chai, Hong Kong

321/2023 T/J(489/2023)

電話

Tel.

傳真 For

: 2824 0578

24 August 2023



來函檔號

Your ref.

#### Approval of "DELABIE" Self Closing Tap (General Acceptance No. B20230009)

Your letter ref. 740500 dated 9 May 2023 and subsequent submissions received by this department up to 3 August 2023 refer.

It is noted that the fitting described below has been accepted by the United Kingdom Water Regulations Advisory Scheme (WRAS) to have complied with the requirements of the United Kingdom Water Supply (Water Fittings) Regulations / Scottish Water Byelaws when correctly installed. This Authority accepts that the fitting described below based on the WRAS certificate and test report ref. J28688r1 issued on 5 June 2023 by Nutek Systems (HK) Limited complies with, and its use when correctly installed does not contravene, the Waterworks Ordinance and Regulations.

Name of Manufacturer:

Delabie SAS

Country of Origin:

France

Brand:

Delabie

Details of Fitting:

1/2" Self closing tap

Model:

740500

**Body Markings:** 

DELABIE





WRAS Approval Number: 2304074

Installation Requirements: R001, R006

(Appendix A of WRAS approval letter refers)

**Expiry Date:** 

15 March 2028

In view of the acceptance by WRAS, this Authority has no objection to the use of the said fitting in fresh water plumbing systems subject to full adherence to Waterworks installation requirements. In particular, you are required to draw your customers' attention to the following installation requirements –

"Installation shall comply with the 'Installation Requirements & Notes' of the WRAS's approval letter concerned."

A condition of this acceptance is that the fitting to be installed should be replicas of the sample certified by WRAS and no modification should be made to the fitting. This acceptance may be withdrawn at any time if the standard of the fitting installed fails to meet that of the approved sample or if the fitting is found to be unsuitable for use in fresh water plumbing systems.

This acceptance is only applicable to the main body of the fitting, unless otherwise specified.

For the use of the fitting in any project, the General Acceptance Number of this letter must be quoted as a means of identification of acceptance of the fitting by this Authority.

Should you have any enquiries, please contact our Engineer Ms Winnie LO at tel. no. 3583 4086.

Yours faithfully,

(YAU Hau Yin)

for Director of Water Supplies

Encl.

c.c. WSD 3321/1/82 ] - without catalogue ME/MC ] - with soft copy only