

# Acme Sanitary Ware Co. Ltd.

1/F, Acme Building, 22-28 Nanking Street, Kowloon, Hong Kong Tel: 2388 7171 Fax: 2710 8012 Email: acme@acmesanitary.com.hk Website: www.acmesanitary.com.hk

PROJECT	REF	REV	ITEM CODE	
LOCATION	DATE		PAGE	

# SANITARY WARE SPECIFICATION SHEET

Bobrick (USA) "Classic Series" Double-roll toilet tissue dispenser with controlled delivery			
Refer to drawing			
B-274			
Heavy-duty cast aluminum/ Satin			
Bobrick Washroom Equipment Inc. (USA)			
Acme Sanitary Ware Co. Ltd Mr. Eric Wong/ Mr. Don Yuen			
(852) 2388-7171 / (852) 2710-8012 acme@acmesanitary.com.hk www.acmesanitary.com.hk			

# Illustration/ Drawing

### MATERIALS:

**Bracket** — Heavy-duty cast aluminum with satin finish. Small extrusion limits rotation of spindle to 3/4 revolution.

**Spindles (2)** — Molded high-impact ABS. Equipped with retractable pin and concealed locking mechanism.

### OPERATION:

Controlled deliver y of toilet tissue rolls; 3/4 revolution of spindles on each dispensing operation. Counterbalanced spindles automatically return to original position. Eliminates waste. Accommodates two standard-core toilet tissue rolls up to 6" (152mm) diameter (2000 sheets). Spindles can only be removed with special key furnished. Theft-resistant.

# INSTALLATION:

For partitions with particle-board or other solid core, provide sheet-metal screws or through-bolts, nuts, and washers.


For hollow-core metal partitions, provide solid backing into which sheet-metal screws can be secured. If two units are installed back-to-back, then provide threaded sleeves and machine screws for the full thickness of partition.

For plaster or dr y wall construction, provide concealed backing to comply with local building codes, then secure unit with sheet-metal screws.

For other wall surfaces, provide sheet-metal screws and fiber plugs or expansion shields, or provide 1/8" (3mm) toggle bolts or expansion bolts.

## SPECIFICATION:

Double-roll toilet tissue dispenser shall have a heavy-duty cast-aluminum bracket with satin finish. Theftresistant spindles shall be molded high-impact ABS with retractable pins and concealed locking mechanisms. Unit shall accommodate two standard-core toilet tissue rolls up to 6" (152mm) diameter (2000 sheets) and provide controlled delivery operation.



Note: