



Acme Sanitary Ware Co. Ltd.

1/F, Acme Building, 22-28 Nanking Street, Kowloon, Hong Kong

Tel: 2388 7171 Fax: 2710 8012


Email: acme@acmesanitary.com.hk

Website: www.acmesanitary.com.hk

Since 1949

| | | | | | | |
|----------|--|------|--|-----|-----------|--|
| PROJECT | | REF | | REV | ITEM CODE | |
| LOCATION | | DATE | | | PAGE | |

SANITARY WARE SPECIFICATION SHEET

| | | |
|---|---|---|
| Item Descriptions | Bobrick (USA) Tilt mirror with stainless steel frame | Illustration/ Drawing |
| Dimensions | L460 x W100 x H920mm | |
| Model | B-293 1836 | |
| Material/ Finish | Heavy Gauge Stainless Steel/ Satin | |
| Manufacturer | Bobrick Washroom Equipment Inc. (USA) | |
| Supplier | Acme Sanitary Ware Co. Ltd Mr. Eric Wong/ Mr. Don Yuen | |
| Contact Tel/Fax | (852) 2388-7171 / (852) 2710-8012 | |
| E-mail | acme@acmesanitary.com.hk | |
| Website | www.acmesanitary.com.hk | |
| <p>Frame — 18-8 S, type 304, heavy-gauge stainless steel with satin finish. Tapers from 4" (100mm) depth at top to 1" (25mm) depth at bottom. Bevel design on front holds frame tightly against mirror. Corners are welded, ground, and polished smooth. Galvanized steel back and inner stiffener frame is one-piece welded construction with slots for mounting screws and integral screw-head lock.</p> <p>Designer's Note: Type 304 stainless steel provides superior corrosion resistance, compared to 400 Series stainless steel, against environmental moisture, hose-down maintenance and strong cleaning solutions.</p> <p>Mirror — No. 1 quality, 1/4" (6mm) select float glass, selected for silvering; electrolytically copper-plated by the galvanic process, guaranteed for 15 years against silver spoilage. All edges are polished and protected by plastic filler strips; back is protected by full-size, shock-absorbing, water-resistant, nonabrasive, 1/8" (3mm) thick polystyrene padding.</p> | |  <p>The illustration shows a vertical rectangular mirror with a stainless steel frame. A technical drawing to the right provides detailed dimensions: overall width is 18" (46cm), top depth is 4" (100mm) tapering to 1" (25mm) at the bottom. Mounting slots are 2-3/8" (60mm) apart. The mirror is 36" (91cm) high. A recommended mounting height of 69-1/2" (1765mm) is indicated for barrier-free design. The frame has a 1-1/2" (40mm) top flange and a 1-3/4" (45mm) bottom flange. The mirror is secured with 3/4" (19mm) screws.</p> |

Note:

* All information of the above is for the reference only. No prior notice is made if any changes.

Source: Bobrick Washroom Equipment Inc.