



Acme Sanitary Ware Co. Ltd.

1/F, Acme Building, 22-28 Nanking Street, Kowloon, Hong Kong
 Tel: 2388 7171 Fax: 2710 8012
 Email: acme@acmesanitary.com.hk
 Website: www.acmesanitary.com.hk

PROJECT		REF		REV	ITEM CODE	
LOCATION		DATE			PAGE	

SANITARY WARE SPECIFICATION SHEET

Item Descriptions	Bobrick (USA) Stainless steel recessed sharp disposal in satin finish (Capacity: 5.11L)
Dimensions	L349 x W130 x H486 mm
Model	B-35016
Finish	Satin Finish
Material	Stainless Steel
Manufacturer	Bobrick Washroom Equipment Inc. (USA)
Supplier	Acme Sanitary Ware Co. Ltd Mr. Eric Wong/ Mr. Wilson Hung
Contact Tel/Fax	(852) 2388-7171 / (852) 2710-8012
E-mail	acme@acmesanitary.com.hk
Website	www.acmesanitary.com.hk

MATERIALS:

Cabinet — Heavy gauge stainless steel. All welded construction.
Door — 22 gauge stainless steel with exposed surfaces in #4 satin finish. Heavy-duty stainless steel piano-hinge. Tumbler lock keyed like other Bobrick accessories.
Flange — 22 gauge stainless steel beveled flange with exposed surfaces in #4 satin finish. One-piece seamless construction, 1" wide with 1/4" return.
Container — BD Brand (Becton, Dickinson and Company) Sharps Collector, 5.4 Qt, part number 305443 (not furnished by manufacturer).

OPERATION:

Needle disposal unit installed/removed by locked hinged door. Needle disposal unit supplied by others. Door must open down 180° for installation / removal of needle disposal.

INSTALLATION:

Requires rough wall opening 12" W x 17 3/8" H x 5" D. Secure to framing with four mounting screws (not included) at holes provided. The top 2 mounting screws should be flat-head screws. Shim at screw points as required.

SPECIFICATION:

Sharps disposal shall be fabricated of stainless steel with exposed surfaces in satin finish. Door secured by piano-hinge. Removable needle disposal with tumbler lock.

Dimensions:

- Top mounting hole spacing: 4-7/8" (124mm)
- Top width: 13-3/4" (349mm)
- Overall height: 19-1/8" (486mm)
- Overall width: 11-3/4" (299mm)
- Internal height to top of container: 11-17/64" (268mm)
- Internal width: 11-3/4" (299mm)
- Internal height to bottom of container: 17-3/16" (453mm)
- Internal width to door edge: 6" (152mm)
- Bottom door offset: 2" (51mm)
- Bottom door offset: 1/4" (6.4mm)
- Door thickness: 5-1/8" (130mm)

Rough Wall Opening:
 12" (305mm) wide
 17-3/8" (441mm) high
 5" (127mm) minimum recessed depth

Recommended Mounting Height Off Floor for Universal / Accessible Design:
 38" to 48" (965 to 1219mm)

Note:

* All information of the above is for the reference only. No prior notice is made if any changes.