



# Acme Sanitary Ware Co. Ltd.

1/F, Acme Building, 22-28 Nanking Street, Kowloon, Hong Kong  
 Tel: 2388 7171 Fax: 2710 8012  
 Email: acme@acmesanitary.com.hk  
 Website: www.acmesanitary.com.hk

PROJECT		REF		REV	ITEM CODE	
LOCATION		DATE			PAGE	

## SANITARY WARE SPECIFICATION SHEET

<p><b>Item Descriptions</b></p> <p><b>Dimensions</b></p> <p><b>Model</b></p> <p><b>Material/ Finish</b></p> <p><b>Manufacturer</b></p> <p><b>Supplier</b></p> <p><b>Contact Tel/Fax</b></p> <p><b>E-mail</b></p> <p><b>Website</b></p>	<p>Bobrick (USA) Stainless steel recessed waste receptacle in satin finish</p> <p>L440 x W212 x H1018 mm</p> <p>B-35643</p> <p>Stainless Steel / Satin Finish</p> <p>Bobrick Washroom Equipment Inc. (USA)</p> <p>Acme Sanitary Ware Co. Ltd Mr. Eric Wong/ Mr. Don Yuen</p> <p>(852) 2388-7171 / (852) 2710-8012 acme@acmesanitary.com.hk www.acmesanitary.com.hk</p>	<p><b>Illustration/ Drawing</b></p>										
<p><b>MATERIALS:</b></p> <p><b>Cabinet</b> —18-8, Type-304, heavy-gauge stainless steel. All-welded construction. Exposed surfaces have satin-finish.</p> <p><b>Door</b> —18-8, Type-304, 18-gauge (1.2mm) stainless steel with satin-finish. Secured to cabinet with a concealed, full-length stainless steel piano-hinge. Equipped with two tumbler locks keyed like other Bobrick washroom accessories.</p> <p><b>Waste Receptacle</b> — Leak-proof, rigid molded plastic waste receptacle. Removable for servicing. Capacity: 12-gal. (45.4-L).</p> <p><b>OPERATION:</b> To service waste receptacle, unlock door with key provided and remove waste container. Cable door-swing limiter prevents damage to washroom accessories and walls.</p> <p><b>INSTALLATION:</b> Provide framed rough wall opening 15-3/4" wide x 38-1/2" high (400 x 978mm). Minimum recessed depth required from finish face of wall is 7-11/16" (195mm). Allow clearance for construction features that may protrude into rough wall opening from opposite wall. Coordinate with mechanical engineer to avoid pipes, vents, and conduits in wall. Mount cabinet with shims between framing and cabinet at all points indicated by an S, then secure unit with (4) #10 x 1-1/4" (4.8 x 32mm) sheet-metal screws (not furnished).</p> <p><b>Replacement Parts:</b></p> <table border="1" data-bbox="98 1657 558 1836"> <tr> <td>Knob Latch</td> <td>314370-22</td> </tr> <tr> <td>Skirt Kit</td> <td>35649-53</td> </tr> <tr> <td>Door Replacement Kit</td> <td>35649-73</td> </tr> <tr> <td>Lock and Key</td> <td>39003-21</td> </tr> <tr> <td>Plastic Waste Receptacle</td> <td>39003-31</td> </tr> </table> <div data-bbox="571 1657 861 1792" style="border: 1px solid black; padding: 5px;"> <p><b>Rough Wall Opening</b>          15-3/4" (400mm) wide          38-1/2" (978mm) high          7-11/16" (195mm) min depth</p> </div> <p><b>SPECIFICATION:</b> Recessed waste receptacle shall be Type-304 stainless steel with all-welded construction; exposed surfaces shall have satin finish. Door shall be Type-304, 18 gauge (1.2mm) secured to cabinet with a concealed, full-length stainless steel piano-hinge, cable door-swing limiter and equipped with two tumbler locks keyed like other Bobrick washroom accessories. Waste receptacle shall be furnished with a removable, leak-proof, rigid molded plastic waste-container with a minimum capacity of 12-gal. (45.4-L).</p>		Knob Latch	314370-22	Skirt Kit	35649-53	Door Replacement Kit	35649-73	Lock and Key	39003-21	Plastic Waste Receptacle	39003-31	
Knob Latch	314370-22											
Skirt Kit	35649-53											
Door Replacement Kit	35649-73											
Lock and Key	39003-21											
Plastic Waste Receptacle	39003-31											

**Note:**

\* All information of the above is for the reference only. No prior notice is made if any changes.