



Acme Sanitary Ware Co. Ltd.

1/F, Acme Building, 22-28 Nanking Street, Kowloon, Hong Kong
 Tel: 2388 7171 Fax: 2710 8012
 Email: acme@acmesanitary.com.hk
 Website: www.acmesanitary.com.hk

PROJECT		REF		REV	ITEM CODE	
LOCATION		DATE			PAGE	

SANITARY WARE SPECIFICATION SHEET

<p>Item Descriptions</p> <p>Dimensions</p> <p>Model</p> <p>Material/ Finish</p> <p>Manufacturer</p> <p>Supplier</p> <p>Contact Tel/Fax</p> <p>E-mail</p> <p>Website</p>	<p>Bobrick (USA) Stainless steel surface-mounted waste receptacle in satin finish (Capacity: 45.4L)</p> <p>L440 x W215 x H1020 mm</p> <p>B-35649</p> <p>Stainless Steel / Satin Finish</p> <p>Bobrick Washroom Equipment Inc. (USA)</p> <p>Acme Sanitary Ware Co. Ltd Mr. Eric Wong/ Mr. Wilson Hung</p> <p>(852) 2388-7171 / (852) 2710-8012 acme@acmesanitary.com.hk www.acmesanitary.com.hk</p>	<p>Illustration/ Drawing</p> <p>Technical drawing showing dimensions in inches and millimeters:</p> <ul style="list-style-type: none"> Top width: 17-3/8" (440mm) Top opening width: 10-11/16" (270mm) Top opening height: 6-3/4" (170mm) Bottom opening width: 13-3/16" (335mm) Bottom opening height: 8-1/16" (205mm) Overall height: 40-1/8" (1020mm) Internal height: 31-7/16" (800mm) Mounting offset from floor: 24" (610mm) Recommended mounting height off floor for universal design: 48" (1220mm) Finish Face of Wall offset: 8 7/16" (215mm) Lock and Key location: 24" (610mm) from bottom opening 										
<p>MATERIALS:</p> <p>Cabinet — 18-8, Type-304, heavy-gauge stainless steel. All-welded construction. Exposed surfaces have satin-finish.</p> <p>Skirt — 18-8, Type-304, stainless steel with satin-finish.</p> <p>Door — 18-8, Type-304, 18-gauge (1.2mm) stainless steel with satin-finish. Secured to cabinet with a concealed, full-length stainless steel piano-hinge. Equipped with two tumbler locks keyed like other Bobrick washroom accessories.</p> <p>Waste Receptacle — Leak-proof, rigid molded plastic waste receptacle. Removable for servicing. Capacity: 12-gal. (45.4-L).</p> <p>OPERATION: To service waste receptacle, unlock door with key provided and remove waste container. Cable door-swing limiter prevents damage to washroom accessories and walls.</p> <p>INSTALLATION: Mount unit on wall with four #10 x 1-1/4" (4.8 x 32mm) sheet-metal screws (not furnished) at points indicated by an S. For plaster or dry wall construction, provide concealed backing to comply with local building codes, then secure unit with sheet-metal screws. For other wall surfaces, provide fiber plugs or expansion shields for use with sheet-metal screws, or provide 3/16" (5mm) toggle bolts or expansion bolts. If unit projects above top of wainscot, provide aluminum channel or other filler to eliminate gap between cabinet and finish face of wall.</p> <p>Replacement Parts:</p> <table border="0"> <tr> <td>Knob Latch</td> <td>314370-22</td> </tr> <tr> <td>Skirt Kit</td> <td>35649-53</td> </tr> <tr> <td>Door Replacement Kit</td> <td>35649-73</td> </tr> <tr> <td>Lock and Key</td> <td>39003-21</td> </tr> <tr> <td>Plastic Waste Receptacle</td> <td>39003-31</td> </tr> </table> <p>SPECIFICATION: Surface-mounted waste receptacle shall be Type-304 stainless steel with all-welded construction; exposed surfaces shall have satin finish. Door shall be Type-304, 18 gauge (1.2mm) secured to cabinet with a concealed, full-length stainless steel piano-hinge, cable door-swing limiter and equipped with two tumbler locks keyed like other Bobrick washroom accessories. Waste receptacle shall be furnished with a removable, leak-proof, rigid molded plastic waste-container with a minimum capacity of 12-gal. (45.4-L).</p>		Knob Latch	314370-22	Skirt Kit	35649-53	Door Replacement Kit	35649-73	Lock and Key	39003-21	Plastic Waste Receptacle	39003-31	
Knob Latch	314370-22											
Skirt Kit	35649-53											
Door Replacement Kit	35649-73											
Lock and Key	39003-21											
Plastic Waste Receptacle	39003-31											

Note:

* All information of the above is for the reference only. No prior notice is made if any changes.

Source: Bobrick