



Acme Sanitary Ware Co. Ltd.

1/F, Acme Building, 22-28 Nanking Street, Kowloon, Hong Kong

Tel: 2388 7171 Fax: 2710 8012

Email: acme@acmesanitary.com.hk

Website: www.acmesanitary.com.hk

Since 1949

PROJECT		REF		REV	ITEM CODE	
LOCATION		DATE			PAGE	

SANITARY WARE SPECIFICATION SHEET

<p>Item Descriptions</p> <p>Dimensions</p> <p>Model</p> <p>Material/ Finish</p> <p>Manufacturer</p> <p>Supplier</p> <p>Contact Tel/Fax</p> <p>E-mail</p> <p>Website</p>	<p>Bobrick (USA) Toilet brush holder</p> <p>Refer to drawing</p> <p>B-544</p> <p>Stainless Steel/ Satin</p> <p>Bobrick Washroom Equipment Inc. (USA)</p> <p>Acme Sanitary Ware Co. Ltd Mr. Eric Wong/ Mr. Don Yuen</p> <p>(852) 2388-7171 / (852) 2710-8012</p> <p>acme@acmesanitary.com.hk</p> <p>www.acmesanitary.com.hk</p>	<p style="text-align: center;">Illustration/ Drawing</p> <div style="text-align: right;"> </div> <p>The drawing includes the following dimensions and labels:</p> <ul style="list-style-type: none"> Finished Face of Wall: 10mm (3/8") Toilet Brush: 90mm (3-9/16") Plastic Liner Wall Mounting Bracket: 125mm (5") Stainless Steel Cylinder: 40mm (1-5/8") 50mm (2") 30mm (1-1/4") 85mm (3-3/8") 405mm (16") 105mm (4-1/16") 95mm (3-3/4") Cylinder Mounting Screw: 2 Required (secures Cylinder to Wall Bracket)
<p>MATERIAL:</p> <p>Toilet Brush — 18-8, type-304, 9.5mm (3/8") diameter, stainless steel, threaded into toilet brush head.</p> <p>Plastic Liner — Leak-proof molded polyethylene. Supports Toilet Brush to maintain it in a vertical position. Removable for cleaning.</p> <p>Cylinder — 18-8, type-304, 1.2mm (18-gauge) stainless steel, seamless construction.</p> <p>Wall Bracket — 18-8, type-304, 1.5mm (16-gauge) stainless steel. Equipped with screws to secure cylinder.</p> <p>INSTALLATION:</p> <p>For plaster or dry wall construction, provide concealed backing to comply with local building codes, then secure unit with sheet-metal screws (not furnished). For other wall surfaces, provide fiber plugs or expansion shields for use with sheet-metal screws (not furnished), or provide 3mm (1/8") toggle bolts or expansion bolts.</p> <p>For partitions with particle-board or other solid core, secure with sheet-metal screws (not furnished), or provide through-bolts, nuts, and washers. For hollow-core metal partitions, provide solid backing into which the sheet-metal screws (not furnished) can be secured.</p> <p>SPECIFICATION:</p> <p>Toilet Brush Holder shall be type-304 stainless steel with _____ (insert one satin finish or bright polished) finish. Toilet Brush Holder shall have 9.5mm (3/8") diameter toilet brush handle threaded into toilet brush. Unit shall be equipped with a removable, leak proof plastic liner to hold toilet brush in vertical position. Cylinder shall be 1.2mm (18-gauge), seamless construction. Cylinder shall be secured to the wall with screws secured into wall plate.</p>		<p><input type="checkbox"/> B-544 Satin-finish stainless steel</p> <p><input type="checkbox"/> B-5446 Bright Polished stainless steel</p>

Note:

* All information of the above is for the reference only. No prior notice is made if any changes.

Source: Bobrick Washroom Equipment Inc.