









PROJECT		REF		REV	ITEM CODE	
LOCATION		DATE			PAGE	







SANITARY WARE SPECIFICATION SHEET

Item Descriptions	FASTDRY (Taiwan) wall mounted high speed hand dryer In white epoxy Finish ; slim design 100mm depth	Illustration/ Drawing
Dimensions	W275 x D100 x H216 mm	  
Model	ECOSLENDER 01	
Finish :	White Epoxy Finish	
Manufacturer	FASTDRY (Taiwan)	
Supplier	Acme Sanitary Ware Co. Ltd Mr. Eric Wong/ Mr. Don Yuen	
Contact Tel/Fax	(852) 2388-7171 / (852) 2710-8012	
E-mail Website	acme@acmesanitary.com.hk www.acmesanitary.com.hk	
<p>EcoSlender01 ADA compliant 1000W White Slim Hand Dryer EcoSlender01 is a slim white painted ADA high speed hand dryer. Since most sinks and toilets are white, the color and sleek design of EcoSlender hand dryer make it easy to fit in the public restroom. Hokwang is devoted to creating an accessible washroom environment. The main purpose of EcoSlender hand dryer is to make everyone's hand drying experience even more accommodating.</p> <p>EcoSlender hand dryer is ADA-Compliant (Americans with Disabilities Act) ; its thin profile only protrudes 4 inches (10 cm) from the wall. Moreover, EcoSlender hand dryer has patented parallel dual air outlets resulting in high drying efficiency with quiet operation. The slim hand dryer cover design also creates a wide drying area to allow hands to dry both naturally and comfortably.</p> <p>Specification</p> <p>Drying Time: 12 seconds (According to hand dryer PCR) Operating Voltage: 110V-120Vac, 50/60 Hz, 0.84-1.0kW Operating Voltage: 220V-240Vac, 50/60 Hz, 0.84-1.0kW Standby Power: 0.3-0.4W Timing Protection: 60 seconds auto shut off Sound Level: MIN 72.8 dB to 77.6 dB MAX @ 1m Air Speed: 70-82 m/s, adjustable Sensing range: 170 mm ± 20 mm, adjustable Drip Proof: IP24 UL, CE, GS, CB, BSMI, EMC, LVD, WEEE, ROHS, GreenSpec certified Patented: Taiwan, China, United States, EU</p> <p>Shipping Information Master Carton Size (W x H x D): 521mm x 370mm x 312mm Shipping Weight: 17.9kgs (39.7lbs)</p>		  WEEE RoHS 

Note:

* All information of the above is for the reference only. No prior notice is made if any changes.

Specs	
	air speed 70-82 m/s
	standby power 0.3-0.4W
	1kW only
	IP 24

Design	
	parallel dual air outlets enhance drying efficiency
	less than 4" from the wall
	heater on/off
	sound & power adjustment
	fewer materials save resource
	recycled and reused

In Use	
	10-15 seconds drying time
	save 80% of energy cost
	three safety protections
	60s timing protection
	easy to clean
	easy maintenance

Cover Finish	EcoSlender01- White Epoxy Finish EcoSlender04, SA06-Bright Finish EcoSlender05, SA07-SatinFinish
Cover Material	EcoSlender01- Steel EcoSlender04, 05, SA06, SA07-Stainless Steel
Packaging (carton)	4 dryers/carton. Gross weight 17.9kg. Measurement 2.1'
Drying Time	Less than 10-15 seconds
Operating Voltage	110V-120Vac, 50/60 Hz, 0.84-1.0kW 220V-240Vac, 50/60 Hz, 0.84-1.0kW
Motor Wattage	325-500W, Adjustable
Standby Power	0.3-0.4W
Air Speed	70-82 m/s, Adjustable
Sound Level	MIN 72.8 dB to 77.6 dB MAX @ 1m
Sensing Range	170 mm ± 20 mm, Adjustable
Drip Proof	IP24
Timing Protection	60 seconds auto shut off
Motor Thermal Protection	Auto resetting thermostat turns unit off, 120V at 135°C(275°F), 240V at 95°C(203°F)
Heater Thermal Protection	Auto resetting thermostat turns unit off at 85°C(185°F) Thermal fuse cuts unit off at 142°C(288°F)

Safety Approvals

