



PROJECT		REF		REV	ITEM CODE	
LOCATION		DATE			PAGE	

SANITARY WARE SPECIFICATION SHEET

<p>Item Descriptions</p>	<p>American Standard (PRC) Chrome plated extended sensor faucet with Line-Sensor Technology, 6V alkaline battery DC</p>	<p>Illustration/ Drawing</p>
<p>Dimensions</p>	<p>L163 x W55 x H242 mm</p>	
<p>Model</p>	<p>FFAS8510-D00500BC0</p>	
<p>Finish</p>	<p>Chrome Plated</p>	
<p>Manufacturer</p>	<p>American Standard (PRC)</p>	
<p>Source</p>	<p>Acme Sanitary Ware Co. Ltd Mr. Eric Wong / Mr. Wilson Hung</p>	
<p>Contact Tel/Fax</p>	<p>(852) 2388-7171 / (852) 2710-8012</p>	
<p>E-mail</p>	<p>acme@acmesanitary.com.hk</p>	
<p>Website</p>	<p>www.acmesanitary.com.hk</p>	
<p>Line sensor at the spout With PCA aerator to ensure stable water flow under high pressure Safety stop at 59 sec 6V alkaline battery</p> <ul style="list-style-type: none"> • Consisting of 64-light receiving elements mounted in a straight line at the spout, American Standard's Line Sensor comes equipped with Image Processing Technology to provide unmatched sensor precision compared to a conventional sensor faucet. • The streamlined designed faucets also feature aerated water flow to prevent water splashing, offering you an unparalleled experience of both aesthetics and performance for your commercial projects. 		

Note: Equivalent to WF-8510.D00 / CF-8510.D00.50

* All information of the above is for the reference only. No prior notice is made if any changes.



Acme Sanitary Ware Co. Ltd.

1/F, Acme Building, 22-28 Nanking Street, Kowloon, Hong Kong





Tel: 2388 7171 Fax: 2710 8012

Email: acme@acmesanitary.com.hk

Website: www.acmesanitary.com.hk

Since 1949

American Standard



No.	Part Code	Part Des. (CN)	Qty.
1	FFZZ8510-A0050BDPL	A37感應面盆龍頭本體	1
2	FF1-CN521A0002699P	起泡器組件 (45.3030.220) (blue)	1
3	FF1-CN521S00000044	感應頭組件	1
4	FF1-CN521N00000269	邁阿密單孔面盆水嘴限位螺釘	1
5	FF1-CN521Z00000264	感應頭固定座	1
6	FF1-CN521Z00000287	進水管卡環	1
7	FF1-CN521T00000038	PVC進水管 (1M)	1
8	FF1-CN521G00000123	平墊片 ?41.5* ?37.5*2	1
9	FF1-CN521J00000424	牙管 (A921899)	1
10	FF1-CN521G00000035	平墊片 ?48* ?39*2.5	1
11	FF1-CN521Z00000062	邁阿密高腳面盆水嘴緊固板 (606652)	1
12	FF1-CN521J00000500	墊圈	1
13	FF1-CN521N00000296	螺母 M33*1.5 &=9 完成品	1
14	FF1-CN521J00000146	出水接頭	1
15	FF1-CN521S00000011	整流器	1
16	FF1-CN521G00000034	平墊片 ?18.5* ?13*2	3
17	FF1-CN521S00000001	電磁閥	1
18	FF1-CN521N00000131	螺釘 (ST4.2X8)	4
30	FF1-CN521F00000048	控制盒上蓋	1
31	FF1-CN521N00000239	木螺絲	1
32	FF1-CN521Z00000286	控制盒體	1
33	FF1-CN521G00000306	密封扣	1
34	FF1-CN521Z00000081	電線孔塞	1
35	FF1-CN521F00000181	固定板	1
36	FF1-CN521Z00000080	控制盒孔塞	1
37	FF1-CN521F00000059	電池盒上蓋	1
38	FF1-CN521G00000085	電池盒上蓋密封圈	1
39	FF1-CN521S00000045	交流板電源板元件	1
40	FF1-CN521G00000086	電池盒主體密封圈	1
41	FF1-CN521Z00000057	電池盒主體	1
42	FF1-CN521Z00000079	電池盒孔塞	1
43	FF1-CN522S00000399	交流電源	4
44	FF1-CN521T00000008	進水軟管 1/2inch*45	1

* All information of the above is for the reference only. No prior notice is made if any changes.



水務署
Water Supplies Department

總部 Headquarters

香港灣仔告士打道七號入境事務大樓 48 樓

48/F, Immigration Tower, 7 Gloucester Road, Wan Chai, Hong Kong

本署檔號
Our ref.
來函檔號
Your ref.



2024 T/J(901/2024)

電話 :
Tel. :
傳真 : 2824 0578
Fax. :

30 October 2024



**Approval of "AMERICAN STANDARD" Sensor Tap
(General Acceptance No. C20240774)**

Your E-Application [file-id: ETJ-GA-20240821-242] dated 6 September 2024 and subsequent submission received by this department on 5 October 2024 refer.

Having considered the test reports ref. 221005PC230178A and 202535EN222816 issued on 4 October 2024 and 4 September 2023 by Fugro Technical Services Ltd., this Authority accepts that the fitting described below complies with, and its use when correctly installed does not contravene, the Waterworks Ordinance and Regulations.

- Name of Manufacturer:** Jiangmen LIXIL AS Sanitary Fitting Manufacturing Co Ltd
- Country of Origin:** the Mainland of China
- Brand:** American Standard
- Details of Fitting:** 1/2" Deck mounted sensor tap with 1 no. of flexible hose
- Model:** FFAS8510-YY0XXXBC0
(where "YY" denotes code of power supply, "XXX" denotes the code of colour)



Body Markings: *American
Standard*

Expiry Date: 2 March 2028

This Authority hereby permits the use of the above fitting in fresh water plumbing systems subject to full adherence to Waterworks installation requirements. In particular, you are required to draw your customers' attention to the following requirement-

"A stop cock or gate valve must be installed at the upstream of the fitting for manual isolation of water supply." AND

"The main voltage operated sensor valve should comply with the electricity safety regulation for applications in bathroom, toilet etc."

A condition of this acceptance is that the fitting to be installed shall be replicas of the sample as certified by the testing agent mentioned above and without modifications. This acceptance may be withdrawn at any time if the standard of the fitting installed fails to meet that of the approved sample or if the fitting is found to be unsuitable for use in fresh water plumbing systems.

This acceptance is only applicable to the main body of the fitting, unless otherwise specified.

For the use of the fitting in any project, the General Acceptance Number of this letter must be quoted as a means of identification of acceptance of the fitting by this Authority.

Should you have any enquiries, please contact our Engineer Mr Albert CHOW at tel. no. 3583 4086.

Yours faithfully,



(Terry KUNG)

for Director of Water Supplies

Encl.

c.c. WSD 3321/1/82] - without catalogue
ME/MC] - with soft copy only