



| | | | | | | |
|----------|--|------|--|-----|-----------|--|
| PROJECT | | REF | | REV | ITEM CODE | |
| LOCATION | | DATE | | | PAGE | |

SANITARY WARE SPECIFICATION SHEET

| | | |
|-------------------|---|---------------------------|
| Item Descriptions | American Standard (PRC) "Genie" Single functions petal pressure hand spray, Robust shower pressure yet gentle on your skin, EASYCLEAN allows easy removal of limescale, mold or dirt, WATER SAVING for ecological and economical sense ; nominated flow rate 8.4 L/min in WELS Grade 1 ; Registration No. SB 18-0222 | Illustration/ Drawing |
| Model | FFASS505-000440BF0 | |
| Finish | Plastic | |
| Manufacturer | American Standard (PRC) | |
| Source | Acme Sanitary Ware Co. Ltd Mr. Eric Wong / Mr. Wilson Hung | |
| Contact Tel/Fax | (852) 2388-7171 / (852) 2710-8012 | |
| E-mail Website | acme@acmesanitary.com.hk www.acmesanitary.com.hk | |

- WATER SAVING**
Water-saving for ecological and economical sense.
- PETAL PRESSURE**
Robust shower pressure yet gentle on your skin.
- EasyClean**
Allows easy removal of limescale, mold or dirt.

| Dynamic flow pressure (kPa) | 50 | 150 | 250 | 350 | 500 |
|-----------------------------|------|------|------|------|------|
| Flow rate (l/min) | 6.28 | 7.93 | 8.33 | 8.80 | 8.83 |

Aquamarine
FFASS505-000600BF0

Petal Pink
FFASS505-000560BF0

Steel Grey
FFASS505-000440BF0

<https://www.youtube.com/watch?v=2z2JVmedejo>
<https://www.youtube.com/watch?v=UvL0PZd95w8>



| | | | | | | |
|----------|--|------|--|-----|-----------|--|
| PROJECT | | REF | | REV | ITEM CODE | |
| LOCATION | | DATE | | | PAGE | |

SANITARY WARE SPECIFICATION SHEET

Genie
MORE PLEASURE.
WHATEVER THE PRESSURE.

Genie hand shower boosts water pressure using a simple principle: water passing through a narrow, tapering channel will always be faster than through a straight, wide one.

- When you cover part of a garden hose nozzle with your finger, water builds up pressure and exits faster. Genie works on the same principle.
- First, the tapered design at the internal water channel becomes >77% narrower before the water reaches the shower face.
- The water pressure is significantly boosted as it exits the shower face via 120 micro spray holes - that taper by 63% over a short depth - with a greater force and speed.

reddot design award winner 2018

American Standard

FEATURES

- Enhanced water pressure for a full, robust shower experience that's gentle on your skin.
- Transparent face plate allows consumers to know if nozzles are blocked.
- Easy to open back cover to wipe off any dirt and/or grime build up.
- Maintenance key included to open back cover.
- Integrated design through dual injection production technique.

SPECIFICATIONS

- With 2.5 GPM Neoperl regulator:
 - 0.10MPa, 4.2 L/min ≤ Q ≤ 8L/min
 - 0.30MPa, Q ≤ 9L/min
- Temperature drop: less than 3°C.
- Under 0.1Mpa, height of spray spouting vertically ≥ 280mm
- Flow at low pressure: Under 0.05Mpa, flow rate ≥ 4.0L/Min
- G1/2 thread
- Three colours to select from: Aquamarine, Petal Pink, Steel Grey

FINISHES AVAILABILITY

- Aquamarine
- Petal Pink
- Steel Grey

SHIPPING WEIGHT

- Net Weight: 0.14 KG
- Gross Weight: 0.24 KG

STANDARDS CRITERIA

- AS W110.0406
- GB/T 23447-2009

註冊號碼 (Registration No.): SB 18-0222



自願參與用水效益標籤計劃 - 沐浴花灑
Voluntary Water Efficiency Labelling Scheme - Showers for Bathing



茲證明
This is to certify that

將下列花灑在本計劃內註冊：
has registered the following shower under this scheme :

| | | |
|--------------------------------|---|--------------------|
| 牌子 / Brand | : | American Standard |
| 型號 / Model | : | FFASS505-000XX0BF0 |
| 原產地 / Country or Region Origin | : | China |

| | | |
|---|---|---|
| 在用水效益標籤上展示的標誌 <i>Symbolic Presentation on the Water Efficiency Label</i> | : |  滴水點 <i>Water droplet(s)</i> |
| 用水效益級別 <i>Water Efficiency Grade</i> | : | 1 |
| 耗水量 <i>Water Consumption</i> | : | 8.4 公升/分鐘 <i>litres/minute</i> |

簽發日期: 31 October 2018
Date of Issue:

 水務署
Water Supplies Department



水務署署長(黃恩諾代行)
for Director of Water Supplies