




Acme Sanitary Ware Co Ltd

Acme Building, 22-28 Nanking Street, Kowloon, Hong Kong
 Tel: 2388 7171 Fax: 2710 8012
 E-mail: acme@acmesanitary.com.hk
 Website: www.acmesanitaryware.com.hk

PROJECT		REF		REV	ITEM CODE	
LOCATION		DATE			PAGE	

SANITARY WARE SPECIFICATION SHEET


Item Descriptions	Mediclinics "Machflow®Plus" (Spain) Steel wall-mounted automatic hand dryer in matte black epoxy finish	<div>Illustration/ Drawing</div> <div><div><div>340 km/h</div><div></div></div><div><div><div>170 mm</div><div>213 mm</div><div>330 mm</div></div><div></div></div></div>																																		
Dimensions	L213 x W170 x H330 mm																																			
Model	M19AB																																			
Material/ Finish	Steel / Matte Black Epoxy Finish																																			
Manufacturer	Mediclinics, S.A. (Spain)																																			
Supplier	Acme Sanitary Ware Co. Ltd Mr. Eric Wong/ Mr. Don Yuen																																			
Contact Tel/Fax	(852) 2388-7171 / (852) 2710-8012																																			
E-mail	acme@acmesanitary.com.hk																																			
Website	www.acmesanitary.com.hk																																			
General description <ul style="list-style-type: none">· Sensor operated high-speed hand dryer with free-maintenance brushless motor, ensuring long lifespan, being ideal for an intensive usage.· With a compact and very robust design, this hand dryer is energetically very efficient and sustainable, providing great energy savings and ultra-fast hand drying. Strongly recommended for high traffic places.· Universal voltage –accepts 100-120 / 220-240 VAC input.· It has an adjustable power motor that regulates energy consumption (between 250 and 1,100W) and provides a maximum air output speed of 340km/h that dries your hands between 8 and 15 seconds.· Optionally, it is also possible to incorporate a quick assembly / disassembly kit for the machine ("Plug-in" kit code KTP009) that allows you to install and uninstall the hand dryer easily, quickly and safely, making maintenance much more efficient and reducing your costs at the same time.· New air concentrator nozzle which helps to channel better the airflow on the hands. Instead of blowing air all over the hands, it focuses the airflow for a more targeted drying. The narrower opening of the concentrator gives the airflow greater pressure on exit, boosting its speed and thus, making the hand drying process much more efficient.· It has an odor neutralizer, code RCPOM14 that aromatizes and deodorizes the environment thanks to its soft fragrance (optional).· Machflow Plus is equipped with an automatic safety disconnection system that switches it off automatically after 60 seconds of continuous use.· It is supplied as standard with all the elements to fix it to a brick wall		<div><div>M19A White epoxy finish</div></div> <div><div>M19AB Matte black epoxy finish</div></div> <div><div>M19AC Bright finish</div></div> <div><div>M19ACS Satin finish</div></div>																																		
		Technical Specifications <table><tr><td>Voltage</td><td>100 - 120V / 220 - 240V</td></tr><tr><td>Frequency</td><td>50/60Hz</td></tr><tr><td>Electrical Isolation</td><td>Class I</td></tr><tr><td>Total power</td><td>250 - 1,100W</td></tr><tr><td>Consumption</td><td>1.3 - 4.8A</td></tr><tr><td>Motor power</td><td>900W</td></tr><tr><td>Rpm</td><td>17,600 - 27,600</td></tr><tr><td>Heating element power</td><td>200W or 0W (ON/OFF switch)</td></tr><tr><td>Dimensions</td><td>330x213x170 mm</td></tr><tr><td>Weight</td><td>5.5Kg</td></tr><tr><td>Cover thickness</td><td>1.5mm</td></tr><tr><td>Drying time</td><td>8-15sec</td></tr><tr><td>Effective airflow</td><td>101 - 177 m³/h (1,680 - 2,950 l/min)</td></tr><tr><td>Air velocity</td><td>220 - 340Km/h</td></tr><tr><td>Air temperature (10 cm distance/23°C)</td><td>42°C</td></tr><tr><td>Sound pressure ^(*) (at 2m)</td><td>67 - 74dBA</td></tr><tr><td>Protection rating</td><td>IP23</td></tr></table>	Voltage	100 - 120V / 220 - 240V	Frequency	50/60Hz	Electrical Isolation	Class I	Total power	250 - 1,100W	Consumption	1.3 - 4.8A	Motor power	900W	Rpm	17,600 - 27,600	Heating element power	200W or 0W (ON/OFF switch)	Dimensions	330x213x170 mm	Weight	5.5Kg	Cover thickness	1.5mm	Drying time	8-15sec	Effective airflow	101 - 177 m ³ /h (1,680 - 2,950 l/min)	Air velocity	220 - 340Km/h	Air temperature (10 cm distance/23°C)	42°C	Sound pressure ^(*) (at 2m)	67 - 74dBA	Protection rating	IP23
Voltage	100 - 120V / 220 - 240V																																			
Frequency	50/60Hz																																			
Electrical Isolation	Class I																																			
Total power	250 - 1,100W																																			
Consumption	1.3 - 4.8A																																			
Motor power	900W																																			
Rpm	17,600 - 27,600																																			
Heating element power	200W or 0W (ON/OFF switch)																																			
Dimensions	330x213x170 mm																																			
Weight	5.5Kg																																			
Cover thickness	1.5mm																																			
Drying time	8-15sec																																			
Effective airflow	101 - 177 m ³ /h (1,680 - 2,950 l/min)																																			
Air velocity	220 - 340Km/h																																			
Air temperature (10 cm distance/23°C)	42°C																																			
Sound pressure ^(*) (at 2m)	67 - 74dBA																																			
Protection rating	IP23																																			

Note:  <https://youtu.be/AtzteMyIIsA>



* All information of the above is for the reference only. No prior notice is made if any changes.

Source: Mediclinics.



SANITARY WARE SPECIFICATION SHEET

Source: Mediclinics.



Acme Sanitary Ware Co Ltd

Acme Building, 22-28 Nanking Street, Kowloon, Hong Kong

Tel: 2388 7171 Fax: 2710 8012

E-mail: acme@acmesanitary.com.hk

Website: www.acmesanitaryware.com.hk

PROJECT		REF		REV	ITEM CODE	
LOCATION		DATE			PAGE	

SANITARY WARE SPECIFICATION SHEET

PLUG-IN SYSTEM

The Machflow® Plug-in technology is an easy, practical, fast and secure system to install and uninstall a hand dryer, making maintenance much more efficient and reducing at the same time its costs.

With the Machflow® Plug-in technology a hand dryer can be installed in a few steps and it can be replaced in less than 10 seconds thanks to its SMED (Single-Minute Exchange of Die) system. Furthermore its maintenance can be carried out better at the maintenance workshop and it is totally secure against electric shocks. All of these benefits allow you to reduce the

This fast install/uninstall technology to the wall is **optional** and it is carried out by means of a special kit code: KTP009.

Installation of the dryer with this system is as follows



The Plug in Kit is compatible with the Machflow hand dryer and the Machflow hairdryer

Unscrew the cover screws (x2)

Remove the cover by a rotating movement

ATTENTION: To prevent electrical shock, disconnect the power source before installing the Plug in Kit

Disconnect the wires and remove the power strip

Unscrew the wall mount screws (x4)

Remove the silent blocks from the back of the unit (x4)

Route the wires through the holes to the back of the unit as shown on the picture

At the back of the unit, connect the wires to the fast connector following the engraved letters (N, L and Earth)

Fix the fast connector to the back of the unit using 2 screws

Close the dryer cover

Screw the cover fixing screws (x2)

Your dryer is now ready to be used on a Plug-in base

Same wall holes may be used for the Plug-in installation

Route the wires through the Plug-in base as shown on the picture

Screw the Plug-in base to the wall (x4)

Connect the wires to the fast connector following the engraved

Fix the fast connector to the Plug-in base using 2 screws

Close the security cover

Your Plug-in base is now ready to be used with a Plug-in dryer

Mount the dryer over the Plug-in base with a from top to down movement

Screw the safety screw

Your dryer is ready to be used

Note: <https://youtu.be/AtzteMyIIsA>



* All information of the above is for the reference only. No prior notice is made if any changes.

Source: Mediclinics,



Acme Sanitary Ware Co Ltd

Acme Building, 22-28 Nanking Street, Kowloon, Hong Kong









Tel: 2388 7171 Fax: 2710 8012

E-mail: acme@acmesanitary.com.hk

Website: www.acmesanitaryware.com.hk

HAND DRYERS

Table

	MODEL	OPERATION		DIMINENSIONS (mm)	Ionizer	HEPA filter media	Drain Pipe	ADJUSTABLE POWER	MOTOR			TRAFFIC FREQUENCY		
		manual	sensor						induction	brush	brushless	HIGH	MEDIUM	LOW
	dualflowplus													
	M24A		•	L320xD228xH665	•	•	•				•	•		
	M24AB		•		•	•	•				•	•		
	M24ACS		•		•	•	•				•	•		
	M14A		•		•	•	•	•		•		•		
	M14AB		•		•	•	•	•		•		•		
	M14ACS		•		•	•	•	•		•		•		
	machflowplus / machflow													
	M19A		•	L213xD170xH330	•	•		•			•	•		
	M19AB		•		•	•		•			•	•		
	M19AC		•		•	•		•			•	•		
	M19ACS		•		•	•		•			•	•		
	M09A		•		•	•		•		•		•		
	M09AB		•		•	•		•		•		•		
	M09AC		•		•	•		•		•		•		
	M09ACS		•		•	•		•		•		•		
	speedflowplus / speedflow													
	M17A		•	L290xD100xH270 (INSIDE CABINET)	•	•		•		•		•		
	M17AB		•		•	•		•		•		•		
	M17AC		•		•	•		•		•		•		
	M17ACS		•		•	•		•		•		•		
	M17AF		•		•	•		•		•		•		
	M06A		•					•		•		•		
	M06AB		•					•		•		•		
	M06AC		•					•		•		•		
	M06ACS		•					•		•		•		
	M06AF		•					•		•		•		
	saniflow													
	E05	•		L276xD214xH245						•		•		
	E05B	•								•		•		
	E05C	•								•		•		
	E05CS	•		L282xD215xH255						•		•		
	E85	•								•		•		
	E88	•								•		•		
	E88B	•		L278xD212xH248						•		•		
	E88C	•								•		•		
	E88CS	•								•		•		
	E88O	•								•		•		
	E05A		•		L276xD214xH245	•					•		•	
	E05AB		•	•						•		•		
	E05AC		•	•						•		•		
E05ACS		•	L282xD215xH255	•					•		•			
E85A		•		•					•		•			
E88A		•		•					•		•			
E88AB		•	L278xD212xH248	•					•		•			
E88AC		•		•					•		•			
E88ACS		•		•					•		•			
E88AO		•		•					•		•			
	mediflow													
	M02A		•	L275xD164xH325	•					•			•	
	M02AB		•		•					•			•	
	M02AC		•		•					•			•	
	M02ACS		•		•					•			•	
	M03A		•		•					•			•	
	M03AB		•		•					•			•	
	M03AC		•		•					•			•	
	M03ACS		•		•					•			•	
	optima													
	M99A		•	L260xD150xH302	•				•				•	
	M99AC		•		•				•				•	
	M99ACS		•		•				•				•	
	juniorplus													
	M88APLUS		•	L253xD150xH303	•				•				•	
	M88PLUS	•		L253xD153xH303					•				•	
	smartflow													
	M04A		•	L147xD138xH259	•					•				•
	M04AC		•		•					•				•
	M04ACS		•		•					•				•

• Optional