



# Acme Sanitary Ware Co Ltd

Acme Building, 22-28 Nanking Street, Kowloon, Hong Kong  
 Tel: 2388 7171 Fax: 2710 8012  
 E-mail: acme@acmesanitary.com.hk  
 Website: www.acmesanitaryware.com.hk

PROJECT		REF		REV	ITEM CODE	
LOCATION		DATE			PAGE	

## SANITARY WARE SPECIFICATION SHEET

<p><b>Item Descriptions</b></p> <p><b>Dimensions</b></p> <p><b>Model</b></p> <p><b>Material/ Finish</b></p> <p><b>Manufacturer</b></p> <p><b>Supplier</b></p> <p><b>Contact Tel/Fax</b></p> <p><b>E-mail</b></p> <p><b>Website</b></p>	<p>Mediclinics (Spain) Toilet paper dispenser, industrial roll, steel black epoxy finish.</p> <p>L310 x W129 x H310 mm</p> <p>PR2787B</p> <p>Steel / Black epoxy Finish</p> <p>Mediclinics, S.A. (Spain)</p> <p>Acme Sanitary Ware Co. Ltd Mr. Eric Wong/ Mr. Don Yuen</p> <p>(852) 2388-7171 / (852) 2710-8012 acme@acmesanitary.com.hk www.acmesanitary.com.hk</p>	<p><b>Illustration/ Drawing</b></p>												
<p><b>Materials &amp; components</b></p> <ul style="list-style-type: none"> <li>PR2787: steel, 0.8 mm thick, white epoxy finish.</li> <li>PR2787C: stainless steel AISI 304, 0.8 mm thick, bright finish.</li> <li>PR2787CS: stainless steel AISI 304, 0.8 mm thick, satin finish.</li> <li>PR2787B: steel, 0.8 mm thick, black epoxy finish.</li> </ul> <p>• One-piece body, 0.8 mm thick, round Ø 300 mm, fully sealed and with a catch system to prevent the opening of the door. The supports of the screws in the back of the appliance, are acting as an anti-moisture support, as well as slots to avoid the screws damaging the toilet paper. It is mounted on the wall by means of 3 wood screws with their corresponding 5 mm wall plugs. It includes a lock system with standard mediclinics® key, that allows opening the lid for replenishment.</p> <p>• PA6 plastic shaft, for standard Ø45mm paper rolls tube, with inertial anti-spin retainer. This shaft is removable with 2 different positions to allow variety of paper rolls. It also allows the use of a standard paper roll in case of need.</p> <p>• One-piece seamless lid, 0.8 mm thick, fully sealed. Fixed to the body by means of rivets that allows swinging down of the lid for the replenishment.</p> <p>• Slot at the front with a plastic viewer that indicates the content level.</p> <p>• Back-plate, 0.6 mm thick, with multiple slots for easy installation. Total compatible with PR0787... series.</p>		<p><b>Technical specifications</b></p> <table border="1"> <tr> <td>Dimensions</td> <td>Ø 300 x 129 mm</td> </tr> <tr> <td>Paper roll capacity</td> <td>Max. Ø 275 mm</td> </tr> <tr> <td>Thickness of body and lid</td> <td>0,8 mm</td> </tr> <tr> <td>Weight (empty)</td> <td>1,70 kg</td> </tr> <tr> <td>Toilet roll width</td> <td>Max. 115 mm</td> </tr> <tr> <td>Toilet roll tube</td> <td>Min. Ø 45 mm</td> </tr> </table>	Dimensions	Ø 300 x 129 mm	Paper roll capacity	Max. Ø 275 mm	Thickness of body and lid	0,8 mm	Weight (empty)	1,70 kg	Toilet roll width	Max. 115 mm	Toilet roll tube	Min. Ø 45 mm
Dimensions	Ø 300 x 129 mm													
Paper roll capacity	Max. Ø 275 mm													
Thickness of body and lid	0,8 mm													
Weight (empty)	1,70 kg													
Toilet roll width	Max. 115 mm													
Toilet roll tube	Min. Ø 45 mm													

Note:

### MOUNTING TEMPLATE

65-75 cm at lower point // 70 cm at lower point (for handicapped people).

