



Acme Sanitary Ware Co Ltd

Acme Building, 22-28 Nanking Street, Kowloon, Hong Kong
 Tel: 2388 7171 Fax: 2710 8012
 E-mail: acme@acmesanitary.com.hk
 Website: www.acmesanitaryware.com.hk



Pure Freude
an Wasser

PROJECT		REF		REV	ITEM CODE	
LOCATION		DATE			PAGE	

SANITARY WARE SPECIFICATION SHEET

Item Descriptions	Grohe (Germany) "Eurosmart Cosmopolitan E" chrome plated wall mounted Infra-red electronic thermostatic temperature control basin mixer with swivel cast spout projection 255mm ;Nominal flow rate 4.4 l/min in WELS Grade 1; Registration No. TM 19-0002					<div>Illustration/ Drawing</div> <div></div> <div></div>											
Model	36333000 (Mixer) 40.2156.000 (Aerator)																
Finish	Chrome Plated																
Brand / Country of Origin	Grohe / Germany																
Source	Acme Sanitary Ware Co. Ltd Mr. Eric Wong/ Mr. Wilson Hung																
Contact Tel/Fax	(852) 2388-7171 / (852) 2710-8012																
E-mail	acme@acmesanitary.com.hk																
Website	www.acmesanitary.com.hk																
<table><tr><td>Dynamic flow pressure (kPa)</td><td>50</td><td>150</td><td>250</td><td>350</td><td>500</td></tr><tr><td>Flow rate (l / min)</td><td>1.60</td><td>3.60</td><td>4.68</td><td>4.85</td><td>5.30</td></tr></table> <ul style="list-style-type: none">• With lithium battery 6 V DC, CR-P2• Wall mountLongLife electronic battery• Swivel cast spout187 mm• Temperature scale handle with safety stop at 100°Fprojection 10"swivel range locking stop at 130°• 7 pre-set programs:• 24/72 hours autoflush• Time or user dependent• Cleaning mode• Safety stop after 60 sec.• Additional functions by remote control:• Adjustable flow time• Adjustable reflection range by remote• Activation of thermal disinfection for 3.5 or 11 min by hand• Multi-stage battery status display• S-unionscovered stop screw• Non-return valve• Dirt strainers• CE approved• Noise classification 1 in accordance with DIN4109 incl. certificate• GROHE TurboStat® thermoelement• GROHE EcoJoy® technology for less water and perfect flow• GROHE StarLight® finishGROHE CoolTouch® metal housing• Min. recommended pressure 15 psi						Dynamic flow pressure (kPa)	50	150	250	350	500	Flow rate (l / min)	1.60	3.60	4.68	4.85	5.30
Dynamic flow pressure (kPa)	50	150	250	350	500												
Flow rate (l / min)	1.60	3.60	4.68	4.85	5.30												
<div></div>																	
<div></div> <div>reddot design award winner 2011</div>																	

* All information of the above is for the reference only. No prior notice is made if any changes.

註冊號碼 (Registration No.): TM 19-0002



自願參與用水效益標籤計劃 - 水龍頭
Voluntary Water Efficiency Labelling Scheme - Water Taps



茲證明

This is to certify that

將下列水龍頭在本計劃內註冊：
has registered the following water tap under this scheme :

牌 子 / Brand	:	GROHE
型 號 / Model	:	36333000 + 40.2156.000
種 類 / Type	:	Mixing
原產地 / Country or Region Origin	:	Germany

在用水效益標籤上展示的標誌

Symbolic Presentation on the Water Efficiency Label



滴水點

Water droplet(s)

用水效益級別

Water Efficiency Grade

1

耗水量

Water Consumption

4.4

公升/分鐘

litres/minute

簽發日期：
Date of Issue:

11 January 2019



水務署

Water Supplies Department



水務署署長(陳仲勤代行)
for Director of Water Supplies



水務署
Water Supplies Department

總部 Headquarters

香港灣仔告士打道七號入境事務大樓七樓
48/F, Immigration Tower, 7 Gloucester Road, Wanchai, Hong Kong



本署檔號 : (2) in WSD 3321/18 Pt.1 T/J(1091)
Our ref.
來函檔號 :
Your ref.

電話 :
Tel.
傳真 : 2824 0578
Fax.

1 November 2018

Dear Sir,

**Approval of "GROHE" Sensor Mixer
(General Acceptance No. C20180732)**

Your letter ref. WRC/1959 dated 20 September 2018 refers.

Having considered the test report ref. J23231A issued on 13 August 2018 by Nutek Systems (HK) Ltd., this Authority accepts that the fitting described below complies with, and its use when correctly installed does not contravene, the Waterworks Ordinance and Regulations.

Name of Manufacturer: Grohe AG
Country of Origin: Germany
Brand: Grohe
Details of Fitting: 1/2" Infra-red electronic basin mixer
Model: 36333000
Body Markings: 
Expiry Date: 8 August 2023



This Authority hereby permits the use of the above fitting in fresh water plumbing systems subject to full adherence to Waterworks installation requirements. In particular, you are required to draw your customers' attention to the following requirement-

"The cold water supply to the fitting shall be drawn from the same source that supplies the hot water apparatus so as to provide a balanced pressure and to obviate the risk of scalding in the event of a restriction or failure in the water supply."

"A stop cock or gate valve must be installed at the upstream of the fitting for manual isolation of water supply." AND

"The main voltage operated sensor valve should comply with the electricity safety regulation for applications in bathroom, toilet etc."

A condition of this acceptance is that the fitting to be installed shall be replicas of the sample as certified by the testing agent mentioned above and without modifications. This acceptance may be withdrawn at any time if the standard of the fitting installed fail to meet that of the approved sample or if the fitting is found to be unsuitable for use in fresh water plumbing systems.

This acceptance is only applicable to the main body of the fitting, unless other specified.

For the use of the fitting in any project, the General Acceptance Number of this letter must be quoted as a means of identification of acceptance of the fitting by this Authority.

Should you have any enquiries, please contact our Engineer Mr. Terry KUNG at tel. no. 3583 4086.

Yours faithfully,



(CHAN Chung-kun)

for Director of Water Supplies

Encl.

c.c. WSD 3321/1/82] - without catalogue
ME/MC] - with soft copy only

