



Acme Sanitary Ware Co. Ltd.

1/F, Acme Building, 22-28 Nanking Street, Kowloon, Hong Kong

Tel: 2388 7171 Fax: 2710 8012

Email: acme@acmesanitary.com.hk

Website: www.acmesanitary.com.hk

PROJECT		REF		REV	ITEM CODE	
LOCATION		DATE			PAGE	

SANITARY WARE SPECIFICATION SHEET

Item Descriptions	Bobrick (USA) Stainless steel recessed sharp disposal in satin finish	<p>Illustration/ Drawing</p> <p>BOBRICK</p>
Dimensions	L349 x W130 x H486 mm	
Model	B-35016	
Material/ Finish	Stainless Steel / Satin Finish	
Manufacturer	Bobrick Washroom Equipment Inc. (USA)	
Supplier	Acme Sanitary Ware Co. Ltd Mr. Eric Wong/ Mr. Don Yuen	
Contact Tel/Fax E-mail Website	(852) 2388-7171 / (852) 2710-8012 acme@acmesanitary.com.hk www.acmesanitary.com.hk	
<p>MATERIALS:</p> <p>Cabinet — Heavy gauge stainless steel. All welded construction.</p> <p>Door — 22 gauge stainless steel with exposed surfaces in #4 satin finish. Heavy-duty stainless steel piano-hinge. Tumbler lock keyed like other Bobrick accessories.</p> <p>Flange — 22 gauge stainless steel beveled flange with exposed surfaces in #4 satin finish. One-piece seamless construction, 1" wide with ¼" return.</p> <p>Container — BD Brand (Becton, Dickinson and Company) Sharps Collector, 5.4 Qt, part number 305443 (not furnished by manufacturer).</p> <p>OPERATION:</p> <p>Needle disposal unit installed/removed by locked hinged door. Needle disposal unit supplied by others. Door must open down 180° for installation / removal of needle disposal.</p> <p>INSTALLATION:</p> <p>Requires rough wall opening 12" W x 17 3/8" H x 5" D. Secure to framing with four mounting screws (not included) at holes provided. The top 2 mounting screws should be flat-head screws. Shim at screw points as required.</p> <p>SPECIFICATION:</p> <p>Sharps disposal shall be fabricated of stainless steel with exposed surfaces in satin finish. Door secured by piano-hinge. Removable needle disposal with tumbler lock.</p>		<p>19-1/8" 486mm</p> <p>11-3/4" 299mm</p> <p>11-17/64" 268mm</p> <p>13-3/4" 349mm</p> <p>4-7/8" 124mm</p> <p>5-1/8" 130mm</p> <p>17-3/16" 453mm</p> <p>6" 152mm</p> <p>2" 51mm</p> <p>1/4" 6.4mm</p> <p>38" to 48" 965 to 1219mm</p> <p>Recommended Mounting Height Off Floor for Universal / Accessible Design</p> <p>Finish Face of Wall</p> <p>Rough Wall Opening 12" (305mm) wide 17-3/8" (441mm) high 5" (127mm) minimum recessed depth</p>

Note:

* All information of the above is for the reference only. No prior notice is made if any changes.

Source: Bobrick