



PROJECT		REF		REV	ITEM CODE	
LOCATION		DATE			PAGE	

SANITARY WARE SPECIFICATION SHEET

<p>Item Descriptions</p> <p>Model</p> <p>Finish</p> <p>Material</p> <p>Manufacturer</p> <p>Source</p> <p>Contact Tel/Fax</p> <p>E-mail</p> <p>Website</p>	<p>Haws (USA) Barrier-free wall-mounted stainless steel electric water cooler</p> <p>HWUACO8</p> <p>Satin</p> <p>Stainless Steel</p> <p>Haws Corporation (USA)</p> <p>Acme Sanitary Ware Co. Ltd Mr. Eric Wong/ Mr. Wilson Hung</p> <p>(852) 2388-7171 / (852) 2710-8012</p> <p>acme@acmesanitary.com.hk</p> <p>www.acmesanitary.com.hk</p>	<p style="text-align: center;">Illustration/ Drawing</p>
<p>Specification:</p> <p>Barrier-free wall-mounted electric water cooler shall include front and side mounted push pads requiring less than 5 pounds of force to activate water flow, satin finish stainless-steel basin, granite color powder-coated galvanized exterior panels, galvanized inner frame, cartridge valve with external adjustment capabilities, and a non-squirt rubber bubbler with a flexible hood. The R-13a refrigeration system is hermetically sealed and delivers a minimum of 8 gph (30.3 lph) of water at 50°F (10°C) cooled from 80°F (26.7°C) inlet water at 90°F (32.2°C) ambient. 115 Volts, 60Hz, rated watts: 460, full load amps: 4.6.</p> <p>Haws electric water coolers are certified to ANSI/NSF Standard 61, Section 9, comply with ARI Standard 1010 and ANSI A117.1, and be listed by Underwriter Laboratories to U.S. and Canadian standards.</p>		

* All information of the above is for reference only. No prior notice is made if any changes. Source: Haws Corporation