



PROJECT		REF		REV	ITEM CODE	
LOCATION		DATE			PAGE	

**SANITARY WARE SPECIFICATION SHEET**

<p><b>Item Descriptions</b></p> <p>American Standard (PRC) "Seva" Exposed bath &amp; shower mixer ; nominated flow rate <b>8 L/min</b> in WELS <b>Grade 1</b> ; Registration No. SB 18-0146</p> <p><b>Dimensions</b></p> <p>L174 x W165 x H188 mm</p> <p><b>Model</b></p> <p>WF-6511.601.50</p> <p><b>Finish</b></p> <p>Chrome Plated</p> <p><b>Manufacturer</b></p> <p>American Standard (PRC)</p> <p><b>Source</b></p> <p>Acme Sanitary Ware Co. Ltd          Mr. Eric Wong / Mr. Don Yuen</p> <p><b>Contact Tel/Fax</b></p> <p>(852) 2388-7171 / (852) 2710-8012</p> <p><b>E-mail</b></p> <p>acme@acmesanitary.com.hk</p> <p><b>Website</b></p> <p>www.acmesanitary.com.hk</p>	<p align="center"><b>Illustration/ Drawing</b></p>																								
<table border="1"> <thead> <tr> <th>Dynamic flow pressure (kPa)</th> <th>50</th> <th>150</th> <th>250</th> <th>350</th> <th>500</th> </tr> </thead> <tbody> <tr> <td>Flow rate (l/min)</td> <td>4.00</td> <td>5.70</td> <td>6.08</td> <td>6.85</td> <td>7.40</td> </tr> </tbody> </table>	Dynamic flow pressure (kPa)	50	150	250	350	500	Flow rate (l/min)	4.00	5.70	6.08	6.85	7.40	<table border="1"> <thead> <tr> <th>Dynamic flow pressure (kPa)</th> <th>50</th> <th>150</th> <th>250</th> <th>350</th> <th>500</th> </tr> </thead> <tbody> <tr> <td>Flow rate (l/min)</td> <td>4.00</td> <td>5.70</td> <td>6.08</td> <td>6.85</td> <td>7.40</td> </tr> </tbody> </table>	Dynamic flow pressure (kPa)	50	150	250	350	500	Flow rate (l/min)	4.00	5.70	6.08	6.85	7.40
Dynamic flow pressure (kPa)	50	150	250	350	500																				
Flow rate (l/min)	4.00	5.70	6.08	6.85	7.40																				
Dynamic flow pressure (kPa)	50	150	250	350	500																				
Flow rate (l/min)	4.00	5.70	6.08	6.85	7.40																				

Note: Same product but different country of origins:-  
 WF-6511.601.50 (PRC) or CF-6511.601.50 (PRC)  
 A-6511-200B (Thailand)

WF-6511.601.50 = WF-6511.611.50 + CF-9015.001.50

\* All information of the above is for the reference only. No prior notice is made if any changes.

註冊號碼 (Registration No.): SB 18-0146




自願參與用水效益標籤計劃 - 沐浴花灑  
Voluntary Water Efficiency Labelling Scheme - Showers for Bathing



茲證明  
This is to certify that

將下列花灑在本計劃內註冊：  
has registered the following shower under this scheme :

牌子 / Brand	:	American Standard
型號 / Model	:	CF-9015.001.50
原產地 / Country or Region Origin	:	China

在用水效益標籤上展示的標誌 <i>Symbolic Presentation on the Water Efficiency Label</i>	:	 滴水點 <i>Water droplet(s)</i>
用水效益級別 <i>Water Efficiency Grade</i>	:	1
耗水量 <i>Water Consumption</i>	:	8 公升/分鐘 <i>litres/minute</i>

簽發日期: 12 June 2018  
Date of Issue:

 水務署  
Water Supplies Department



水務署署長(周世威代行)  
for Director of Water Supplies



水務署

Water Supplies Department

香港灣仔告士打道七號入境

Immigration Tower, 7 Gloucester Road, Hong Kong



電子郵遞

e-mail

wsdinfo@wsd.gov.hk

電話

Telephone

2829 4355

圖文傳真

Facsimile

2824 0578

檔號

Reference

(2) in WSD 3321/17 Pt.1 T/J(930)

11 August 2017

### Approval of "AMERICAN STANDARD" Bath/Shower Mixer

Your letter ref. WRC/1385 dated 6 July 2017 refers.

Having considered the test report ref. J19928 issued on 5 December 2016 by Nutek Systems (HK) Ltd., this Authority accepts that the fitting described below complies with, and its use when correctly installed does not contravene, the Waterworks Ordinance and Regulations.

**Name of Manufacturer:** American Standard

**Country of Origin:** China

**Brand:** American Standard

**Details of Fitting:** 1/2" Single lever bath/shower mixer

**Model:** WF-6511.611.50

**Body Markings:** *American Standard*

**Expiry Date:** 4 December 2021

This Authority hereby permits the use of the above fitting in fresh water plumbing systems subject to full adherence to Waterworks installation requirements. In particular, you are required to draw your customers' attention to the following requirement-

"The cold water supply to the fitting shall be drawn from the same source that supplies the hot water apparatus so as to provide a balanced pressure and to obviate the risk of scalding in the event of a restriction or failure in the water supply." AND

"The shower head or handspray should not be placed in submerged conditions and should be securely fixed to the original position after use."

A condition of this acceptance is that the fitting to be installed shall be replicas of the sample as certified by the testing agent mentioned above and without modifications. This acceptance may be withdrawn at any time if the standard of the fitting installed fails to meet that of the approved sample or if the fitting is found to be unsuitable for use in fresh water plumbing systems.

This acceptance is only applicable to the main body of the fitting, unless other specified.

For the use of the fitting in any project, the Acceptance Reference Number at the bottom of this letter must be quoted as a means of identification of acceptance of the fitting by this Authority.

Should you have any enquiries, please contact our Engineer Mr. Terry KUNG at tel. no. 2294 2656.

Yours faithfully,



(CHAN Chung Kun)  
for Water Authority

c.c.    WSD 3321/1/82    ] - without catalogue  
         ME/MC            ] - with soft copy only